



Contrappeso Shell - 230g¹
Shell Counterweight - 230g¹
Contrapeso Shell - 230g¹
Contrepoids Shell - 230g¹
Gegengewicht - 230g¹
Противовес Shell - 230 Г¹

Fixing Kit¹



Spina intermedia Schuko¹
Schuko piggyback plug¹
Enchufe Schuko intermedio¹
Fiche intermédiaire Schuko¹
Schuko-zwischenstecker¹
Промежуточная розетка Schuko¹

Cavo - Cable 0,52 - 3 - 5 - 10 - 15 - 20 m
Cable - Câble
Kable - Кабель

H07 RN-F 3G1 - Ø 8,8mm (1 function)
H05 RN-F 3X1 - Ø 7,5mm (2 functions)
H07 RN8-F 3G1 - Ø 8,8mm (1 function)
H07 RN-F 3G1 Oil Res.- Ø 8,8mm (1 func.)

Corpo - Casing Polipropilene - Polypropylene
Cuerpo - Corps Polipropileno - Polypropylène
Körper - Корпус Polypropylen - Полипропилен

Alimentazione - Power Supply max.10(8)A 250V
Alimentación - Alimentation électrique
Stromversorgung - Электропитание

Angolo di attivazione - Activation angle 45°
Ángulo de activación - Angle d'activation
Aktivierungswinkel - угол подключения

Profondità - Depth max.10m - 32,8ft
Profundidad - Profondeur
Tiefe - Глубина

Temperatura - Temperature max.+50°C (+122°F)
Temperatura - Température
Temperatur - Температура

Grado di protezione - Protection Grade IP 68
Grado de protección - Degré de protection
Schutzgrad - Класс защиты

Classe - Class I - II
Clase - Classe
Klasse - класс

Certificazioni - Certification
Certificaciones - Homologations
Zulassungen - Сертификация



Type Approved
Safety
Regular Production
Surveillance
www.tuv.com
ID: 1111216897

